

DUPLEX PACKING FILLER AF-1KII



50g - 1kg
Weighing range



Stable
Performance



Easy
Installation

± 2g
Best accuracy



Pneumatic
Cylinder Control



High Speed
Weighing

3600 + Pcs/h
Highest speed



Features:

- **High speed and accuracy:**

the highest speed can reach 3600pcs/h and the best accuracy is ±2g;

- **Granular materials:**

special designed for small weighing range packages, like rice, millet, beans and so on;

- **Stable performance:**

step motor + vibrator feeding-type, pneumatic discharging-type,

- **Parameter setting:**

self-adjust function with target value set only, easy operation.



Specification	
Model	PaxGO AF-1KII
Weighing range	0.05~1Kg
Division	1g
Best Accuracy*	±2g
The highest speed*	3600 pcs/h
Volume	2.8L x 2
Feeding method	Step motor + vibrator feeding-type, pneumatic discharging-type;
Material	Carbon steel/stainless steel optional
Communication	USB, 2*RS485
Pneumatic	0.4~0.6MPa 2m ³ /h
Power	AC 220V ±10%,50/60HZ,400KW
Working environment	0~40°C, 90%R.H condensation is not allowed

*Normally, the diameter of the testing material 1-5mm.

Structure & Dimension Unit: mm

