

# GRANULE PACKING FILLER AF-25K



**5-25 kg**  
Weighing range

**± 10g**  
Best accuracy

**≥ 900** + Pcs/h  
Speed



Stable  
Performance



Easy  
Installation



Servo Motor  
Control



Weighing  
Accurate

## Features:

- **Granular material:** design for plastic particle, granular fertilizer, feeds and other granular material.
- **Easy dismounting:** module design of measuring hopper for easy cleaning;
- **Parameter setting:** self-adjust function with target value set only;
- **Stable performance:** servo motor controls feeding process;
- **Weighing accurate:** weighing range is 5-25kg. Speed can reach 1200 pcs/h when the fast algorithm is opened, and best accuracy ± 10g.



## Optional:



Bag Clamp

- SS304 stainless steel.



10-inch touch screen

- User-friendly interface design, vivid display, easy to operate.

## Specification

Model	PaxGO AF-25K
Weighing range	5~25Kg
Division	1g
Best Accuracy*	±10g
Speed*	≥900pcs/h(Enable fast algorithm:1200 pcs/h)
Volume	55L
Feeding method	Feeding control by servo, pneumatic discharging
Material	SS304,carbon steel
I/O	8 output(5V),8 input(24V)
Communication	RS485,Modbus TCP/IP
Pneumatic	0.4~0.6MPa
Power	Single Phase AC-220V ±10%,50/60HZ,1KW
Working environment	0~40°C , 90%R.H condensation is not allowed

\*Normally, the diameter of the testing material1-5mm.

## Structure & Dimension Unit: mm

