


DYNAMIC CHECKWEIGHER CW-6K

- CW-6K check weigher is suitable for product weight range from 0.5-6kg.
- Weighing accuracy is within $\pm 2g$;
- 10-inch touch screen, can store over 1 million transaction, data export through USB;
- It is widely used for food, feeds, logistic industries, automation production line, and so on.


Multiple industrial application



Feeds



Logistic



Automation production line




6kg

Maximum capacity



$\pm 2g$

Best accuracy



100

Pcs/min
Highest speed



Standard specification

Model	CW-6K
Maximum capacity	6kg
Scale division	0.5g
Best accuracy(3 σ)*	$\pm 2g$
Highest weighing speed*	100pcs/min
Belt speed	10~50m/min
Belt size	500*400mm
Weighing platform height*	750 \pm 50mm
Belt material	PU (blue/white)
Structure of the material	Carbon steel, S304 for weighing platform
Alarm light	3-color signal light (Red, yellow, green)
Display size	10-inch color touch screen
Rejector lineup	Options: swing type, push type, dropping type
Power	AC220V single phase, 50/60Hz, 1275W
Operating temperature	0~40°C
IP grade	IP54, IP65 Optional

*Depend on the weight, size and material of test object.

Dimensions

Unit:mm

