GRANULE PACKING FILLER
AF-25K

5-25 kg
Weighing range

± 10 g
Best accuracy

≥900 + Pcs/h
Speed

Stable Performance

Easy Installation

Servo Motor Control

Weighing Accurate

Features:

- Granular material: design for plastic particle, granular fertilizer. feeds and other granular material.
- Easy dismounting: module design of measuring hopper for easy cleaning;
- Parameter setting: self-adjust function with target value set only;
- Stable performance: servo motor controls feeding process;
- Fast and accurate: weighing range is 5-25kg.Speed can reach 1200 pcs/h when the fast algorithm is opened,and best accuracy ± 10g.

Optional:

Bag Clamp

- SS304 stainless steel.

vibrator feeding

Specification

Model	PaxGO AF-25K
Weighing range	5~25Kg
Division	1g
Best Accuracy*	±10g
Speed*	≥900pcs/h(Enable fast algorithm:1200 pcs/h)
Volume	55L
Feeding method	Feeding control by servo, pneumatic discharging
Material	SS304,carbon steel
I/O	8 output(5V),8 input(24V)
Communication	RS485,Modbus TCP/IP
Pneumatic	0.4~0.6MPa
Power	Single Phase AC-220V ±10%,50/60HZ,1KW
Working environment	0~40°C， 90%R.H condensation is not allowed

*Normally, the diameter of the testing material1-5mm.

Structure & Dimension

Unit: mm



A (Bottom frame dimension)



A (Bottom frame dimension)





B (Feeding port dimension)



B (Feeding port dimension)