


# GRANULE PACKING FILLER AF-10K



**0.5-10kg**  
Weighing range



Stable  
Performance



Easy  
Installation

**±3g**  
Best accuracy



Servo Motor  
Control



Weighing  
Accurate

**≥900** + Pcs/h  
Speed

## Features:

- **Granular material:** design for rice, millet, beans and other granular material;
- **Easy dismounting:** module design of measuring hopper for easy cleaning;
- **Parameter setting:** self-adjust function with target value set only;
- **Stable performance:** servo motor controls feeding process;
- **Fast and accurate:** weighing range is 0.5-10kg. Speed can reach 1300 pcs/h when the fast algorithm is opened, and best accuracy ±3g.

## Optional:



10-inch touch screen

User-friendly interface design,  
vivid display, easy to operate.



## Specification

Model	PaxGO AF-10K
Weighing range	0.5~10Kg
Division	1g
Best Accuracy*	±3g
Speed*	≥900pcs/h(Enable fast algorithm:1300 pcs/h)
Volume	15L
Feeding method	Servo motor+ feeding vibrator, pneumatic discharging
Material	SS304,carbon steel
I/O	8 output(5V),8 input(24V)
Communication	RS485,Modbus TCP/IP
Pneumatic	0.4~0.6MPa
Power	Single Phase AC-220V ±10%,50/60HZ,500KW
Working environment	0~40°C, 90%R.H condensation is not allowed

\*Normally, the diameter of the testing material 1-5mm.

## Structure & Dimension

Unit: mm

