PNEUMATIC VERSION AF-50K



25-50kg Weighing range





Performance

 ± 25 g Best accuracy





Pneumatic Cylinder Control Weighing

≥1100 + Pcs/h

Features:

- Granular material: design for packing plastic particles, rice, sugar and other granular material;
- Easy installation: module design, easy for installation and dismount;
- Convenient setup: self-adjust function with target value set only;
- High-speed performance: pneumatic cylinder control, speed can reach above 1100pcs/h;
- Weighing accurate: weighing range is 25~50kg, best accuracy is ±25g.

Optional:



User-friendly interface design, vivid display, easy to operate.









Division	1g
Best Accuracy*	±25g
Speed*	≥1100pcs/h
Volume	86L
Feeding method	Pneumatic cylinder control
Material	SS304,carbon steel
I/O	8 output(5V),8 input(24V)
Communication	RS485,Modbus TCP/IP
Pneumatic	0.4~0.6MPa
Power	Single Phase AC-220V ±10%,50/60HZ,1KW
Working environment	0~40°C, 90%R.H condensation is not allowed
·	*Normally, the diameter of the testing material1-5mi

PaxGO AF-50K Pneumatic Version

25~50Kg

Structure & Dimension

Specification

Weighing range

Model

Unit: mm

